

## Construction of South County Road 1232

Roadway Improvements to Serve Midland County					
		Quantity	Unit	Unit Price	Total
<b>from SCR 1160 to SCR 1110 - Revised 12/9/2021</b>					
Item	Description				
1	Preparation of R.O.W. (300' ROW)	274	Sta.		
2	Sawcut Existing Asphalt (full depth)	205	L.F.		
3	5 Strand Barb Wire Fence with H Braces	54,581	L.F.		
4	Corner H Braces	8	Ea.		
5	Gates	19	Ea.		
6	Earthwork*	68,988	C.Y.		
7	Haul Off*	22,285	C.Y.		
8	Subgrade Preparation	109,465	S.Y.		
9	Prime Coat**	27,098	Gal.		
10	Flexible Base (Roadway and Driveways)	46,587	C.Y.		
11	HMA Pavement - 3" thickness - Type D**	15,581	Ton		
12	Concrete Pavement at Intersections	578	S.Y.		
13	32'x100' Pitched Concrete Pavement Section	18	Sta.		
14	6" Concrete Driveways	1,570	S.Y.		
15	150'X5' Pipeline Cap	15	Ea.		
16	Reflective Marking (Type 1) 4" Double Yellow Striped	42	Sta.		
17	Reflective Marking (Type 1) 4" Broken Yellow Striped	231	Sta.		
18	Reflective Marking (Type 1) 4" White Striped	274	Sta.		
19	18" Stop Bar Pavement Marking	25	L.F.		
20	Surface Preparation for Pavement Marking	274	Sta.		

## Construction of South County Road 1232

Roadway Improvements to Serve Midland County		Quantity	Unit	Unit Price	Total
<b>from SCR 1160 to SCR 1110 - Revised 12/9/2021</b>					
Item	Description				
21	IN SM RD SN SUP&AM TY10BWG(1) SA (P)	63	Ea.		
22	Aluminum Signs	430	S.F.		
23	RCB - 3' X 2'	76	L.F.		
24	Safety End Treatments (Type I) (2 - RCB 3'x2') (HW=4) (5:1)	3	Ea.		
25	Safety End Treatments (Type I) (2 - RCB 3'x2') (HW=4) (4:1)	1	Ea.		
26	16" HDPE - SDR9	900	L.F.		
27	Erosion Control	1	LS		
28	Traffic Control	1	LS		
29	Mobilization	1	LS		
<b>TOTAL BASE BID FROM SCR 1160 TO SCR 1110</b>					
<b>CONSTRUCTION START DATE FOR SCR 1160 TO SCR 1110</b>					
<b>TOTAL CALENDAR DAYS FOR SCR 1160 TO SCR 1110</b>					

Contractor shall notify the Engineer of Record of any discrepancies in quantities prior to the commencement of construction.

\* Quantities do not include factors for compaction and expansion.

\*\* Rates used for calculation purposes only:

Prime Coat: 0.3 Gal/SY

HMA Pavement - 3" thickness - Type D: 115 lb/SY\*in